

**UK
CA**

1245



11

1245 – CPR – 1010

Strength graded structural timber with rectangular cross section machine (M), Dry Graded (DG), WPCS

Dimensions of cross section: As per delivery notes and invoices

BS EN 14081:2005 + A1:2011

Strength Grade of Timber: **C16**

Source: **UK, ROI**

Reaction to Fire: **D-s2, d0**

Release of Dangerous Substances: **NPD**

Natural Durability (not treated): **Class 4**

For treated timber "PT" Type of: **UC2**

Treatment & Preservative: **Pressure Tanalith E/Tanatone**

Penetration Class: **NP2**

Retention Values: **8.5 kg/m³**

Target Biological Agents: **Insect**

**UK
CA**

1245



11

1245 – CPR – 1010

Strength graded structural timber with rectangular cross section machine (M), Dry Graded (DG), WPCS

Dimensions of cross section: As per delivery notes and invoices

BS EN 14081:2005 + A1:2011

Strength Grade of Timber: **C16**

Source: **UK, ROI**

Reaction to Fire: **D-s2, d0**

Release of Dangerous Substances: **NPD**

Natural Durability (not treated): **Class 4**

For treated timber : **NPD**

Wood Destroying Fungi: **Class 4**

Insects: **NPD**

Termites: **NPD**

Marine Borers: **NPD**